

AD Ø	Locating Rings – Standard Width (mm)													page 2 of 6									
Material thicknesses can in principle be chosen freely. The following values correspond to the current standard.														Further options on request.									
130	5,0	6,0	8,0	9,0	9,5	10,0	11,0	11,5	12,0	12,5	13,0	15,5	18,0										
Mat. Thickness	4	5	4	6	4	4	4	4	4	5	5	5	6										
Option	6								5														
140	4,0	5,0	6,0	8,5	9,0	10,0	11,0	11,2	11,5	12,0	12,5	13,0	16,0										
Mat. Thickness	5	4	5	4	4	4	4	4	4	4	5	5	5										
Option		6			6	5				5													
150	4,0	5,0	5,1	8,5	9,0	10,0	11,0	12,0	12,1	12,5	13,0	15,0	16,5										
Mat. Thickness	5	4	6	6	4	4	4	4	5	5	5	6	6										
Option		6				5		5															
160	2,5	3,0	4,0	5,0	6,3	6,3	8,0	8,5	9,0	10,0	11,0	11,5	12,0	12,1	12,5	13,0	14,0	14,5	16,0	16,2	17,5	18,0	20,5
Mat. Thickness	6	5	5	6	4	4	4	4	4	5	4	4	4	5	5	6	5	5	5	6	6	6	6
Option		5,5	6,5		4,5	4,5	6						5						6				
170	5,0	8,0	8,5	10,0	10,5	11,0	12,5	13,0	14,5	18,0													
Mat. Thickness	6	4	4	5	4	4	5	6	5	6													
Option		6			4,5																		
180	2,5	3,0	4,0	5,0	7,0	7,5	8,0	18,0	11,0	12,0	12,1	12,5	14,5	14,0	18,0	18,5	20,0						
Mat. Thickness	6	5	5	6	7	6	4	5	4	5	5	5	5	6	6	5	6						
Option		6	6,5				6	6,5															
190	5,0	10,0	12,0	15,5	16,5	17,0																	
Mat. Thickness	6	5	5	5	6	6																	
Option		6,5																					
200	2,5	3,0	5,0	6,5	8,0	8,5	9,0	10,0	10,2	11,0	11,2	12,0	12,5	13,0	13,5	14,0	14,5	15,0	16,0	17,0	17,5	21,0	
Mat. Thickness	6	6	6	5	4	6	4	5	4,5	4	4	5	5	6	5	5	5	6	5	6	6	6	
Option		8			6			6,5											6				
210	2,5	5,0	10,0																				
Mat. Thickness	6	6	5																				
Option			6,5																				
215	3,0	5,0	6,5	8,0	8,5	10,0	11,5	12,0	12,5	13,0	14,0	15,0	16,5	18,0	19,5	22,0	22,5	23,0					
Mat. Thickness	6	6	5	4	6	5	4	5	5	6	5	6	6	6	5	6	8	6					
Option	8			6		6,5									6								
225	4,0	5,0	10,0																				
Mat. Thickness	5	6	5																				
Option	6,5		6,5																				

AD Ø	Locating Rings – Standard Width (mm)												page 3 of 6					
Material thicknesses can in principle be chosen freely. The following values correspond to the current standard.													Further options on request.					
230	3,0	5,0	6,5	7,5	10,0	10,0	11,0	12,0	13,0	14,0	15,0	25,0						
Mat. Thickness	6	6	5	7,5	5	8	4	5	5	5	6	6						
Option					6,5				6									
240	5,0	10,0	15,0	16,0	20,0													
Mat. Thickness	6	5	6	5	6													
Option				6														
250	3,0	5,0	10,0	13,0	14,0	15,0	28,0											
Mat. Thickness	6	6	6,5	5	5	6	6											
Option			8															
260	5,0	6,0	6,5	10,0	12,5	14,5	20,5											
Mat. Thickness	6	5	5	6,5	5	5	6											
Option																		
270	5,0	10,0	11,0	13,0	13,5	14,0	14,5	15,0	15,5	16,0	16,5	17,0	17,5	18,5	30,5			
Mat. Thickness	6	6,5	4	6	5	5	5	6	5	5	6	6	6	5	6			
Option										6								
280	3,0	4,0	5,0	7,5	10,0	12,5	14,0	17,0	22,5									
Mat. Thickness	6	8	6	10	6,5	5	5	6	6									
Option		10	10		10			10	8									
290	3,0	5,0	5,5	7,5	10,0	11,5	13,0	15,0	16,0	16,5	17,0	17,5	18,0	20,0	33,0			
Mat. Thickness	6	6	8,5	10	6,5	4	6	6	5	6	6	6	6	6	6			
Option		10			10				6			10			8			
300	3,0	5,0	7,0	10,0	12,0	13,0	15,0	25,0										
Mat. Thickness	6	6	7	6,5	5	6	6	6										
Option		10	10	10														
310	6,0	6,5	10,0	13,0	17,0	18,0	21,0											
Mat. Thickness	5	5	6,5	6	6	6	6											
Option	13		10			10												
320	3,0	5,0	6,0	6,5	8,0	9,0	10,0	15,0	16,0	19,0	20,0	26,5	30,5					
Mat. Thickness	6	6,5	5	5	10	10	6,5	6	6	5	6	8	6					
Option		10	13							10								
340	3,0	4,0	5,0	6,0	9,0	10,0	11,0	12,0	15,0	16,0	16,2	21,0	28,0					
Mat. Thickness	6	6,5	10	5	4	6,5	4	5	6	5	5	6	6					
Option				13	10	10						10						

continued on page 4

AD Ø	Locating Rings – Standard Width (mm)										page 4 of 6
Material thicknesses can in principle be chosen freely. The following values correspond to the current standard.											Further options on request.
360	4,0	6,0	10,0	11,0	12,0	14,0	21,0				
Mat. Thickness	6,5	5	6,5	10	5	5	6				
Option		13	10		10		10				
370	4,0	7,0	10,0	10,5	13,5						
Mat. Thickness	6,5	7	6,5	4	5						
Option	8	10	10	4,5	10						
380	10,0	11,0									
Mat. Thickness	6,5	10									
Option	10										
400	3,0	4,0	8,0	10,0	11,0	12,0	14,0	20,0	22,0	25,0	
Mat. Thickness	6	6,5	6	6,5	4	5	5	6	6	6	
Option	8	8	15	10	10	10	10	10	10	10	
420	10,0	13,0	14,0	28,0							
Mat. Thickness	10	6	5	6							
Option		10	15								
440	4,0	10,0	22,0								
Mat. Thickness	6,5	10	10								
Option	8										
460	5,0	8,0	10,0	10,5	18,0	25,0					
Mat. Thickness	6	6	10	12	6	6					
Option	10	15			10	10					
480	3,0	8,0	10,0	10,5	25,5						
Mat. Thickness	6	10	10	12	6						
Option	8	15			12						
500	3,0	4,0	6,0	10,0	12,5	25,0					
Mat. Thickness	8	8	8,5	10	15	15					
Option	10	10,5	13	20							
520	5,0	8,5	10,0	15,0	16,0						
Mat. Thickness	10	10	10	6	5						
Option	12		20	10	10						
540	9,0	10,0	15,5	16,0	28,0	33,0					
Mat. Thickness	15	10	5	6	12	8					
Option		20	15	10							

continued on page 5

AD Ø **Locating Rings – Standard Width (mm)** page 5 of 6

Material thicknesses can in principle be chosen freely. The following values correspond to the current standard.

Further options on request.

560	10,0	15,0			
Mat. Thickness	10	6			
Option	20	8			
580	10,0	17,5	20,0	26,5	30,0
Mat. Thickness	10	6	15	6	10
Option	20	15		12	
600	10,0	22,0			
Mat. Thickness	10	10			
Option	15				
620	6,0	10,0	16,0	22,0	
Mat. Thickness	8,5	10	6	10	
Option	13	15			
650	10,0	21,5	25,0		
Mat. Thickness	10	15	15		
Option	15				
680	10,0	30,5			
Mat. Thickness	15	15			
Option	20				
700	8,0	10,0	29,5		
Mat. Thickness	15	15	15		
Option		20			
720	10,0	29,5			
Mat. Thickness	10	15			
Option	15				
760	10,0				
Mat. Thickness	15				
Option	20				
780	10,0	30,5			
Mat. Thickness	15	15			
Option	20				
790	10,0				
Mat. Thickness	15				
Option	20				

continued on page 6

AD Ø	Locating Rings – Standard Width (mm)		page 6 of 6
Material thicknesses can in principle be chosen freely. The following values correspond to the current standard.			Further options on request.
820	10,0		
Mat. Thickness	15		
Option	20		
830	10,0		
Mat. Thickness	15		
Option	20		
870	10,0		
Mat. Thickness	15		
Option	20		
865	35,0		
Mat. Thickness	10		
Option			
920	10,0		
Mat. Thickness	15		
Option	20		
980	10,0		
Mat. Thickness	15		
Option	20		
1030	10,0		
Mat. Thickness	20		
Option	25		
1090	10,0		
Mat. Thickness	20		
Option	25		
1090	10,0		
Mat. Thickness	20		
Option	30		

- ▶ For unlisted locating ring types or widths or thicknesses please send us your special request.
 - ▶ Changes and misprints can not be excluded.
-